



Declaration of Performance

Nr. 01156-PYRO-SAFE® BIOFERM-A
PYRO-SAFE® BIOFERM-A

Date: 04.03.2020
Rev.: 01

Page 1 / 1

Unique identification code of the product type

PYRO-SAFE® BIOFERM-A

Intended use

1-component sealant based on acrylic dispersion; non-load-bearing sealant for internal and external applications:
Joints in the facade, type F ext-int (12.5P)

Manufacturer

svt Brandschutz Vertriebsgesellschaft mbH International,
Gluesinger Strasse 86, D - 21217 Seevetal

System for assessing and verifying constancy of performance

System 3 plus 3

Harmonised technical specification

EN 15651-1:2012-12

The notified body

Ginger CEBTP, code number 0074

Declared performance

Essential characteristics	Performance	Harmonised technical specifications
Reaction to fire	Class E	EN 15651-1: 2012-12
Dangerous substances (See safety data sheet for details)	rated	
Steadfastness (EN ISO 7390)	≤ 3 mm	
Volume loss (EN ISO 10563)	≤ 25 %	
Adhesion / cohesion behavior after immersion in water (EN ISO 10591)	≥100%	
Durability (ISO 8339, ISO 9046, ISO 10591)	passed	
Overpaintable (emulsion paints)	passed	EN 13300:2002-11

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above. DoP online available at www.svt.de

Signed for and on behalf of the manufacturer by:

i.V. Christian Meyer-Korte
Product Management Construction

i.A. Daniel Bernhardt
Technical Documentation Construction