



Protect your values.

Mineral fibre boards pre-coated with PYRO-SAFE® FLAMMOTECT-A

Mineral fibre products


Description

The mineral fibre board is a pressure-resistant and water-repellent rock wool insulation board. It is heat and sound insulating, dimensionally stable with temperature changes, vibration damping, chemically neutral and open to diffusion.

The board has a factory-applied pre-coating of the ablative fire protection coating PYRO-SAFE® FLAMMOTECT-A.

Application areas

- Pre-coated mineral fibre boards are used as system boards for cable, pipe and mixed penetration seals approved by the building authorities.



Delivery and packing

PYRO-SAFE® FLAMMOTECT A - Mineral fibre boards			
Packing	Cardboard box	Cardboard box	Cardboard box
Quantity of boards	4	4	4
Coating	On one side		On both sides
Thickness	50 mm	60 mm	60 mm
Item number			
	01181150	01181160	01182160

Please contact us for further information:

✉ global@svt.de

Orders: order@svt.de

☎ +49 4105-40 90-0



Protect your values.

Mineral fibre boards pre-coated with PYRO-SAFE® FLAMMOTECT-A

Technical data

Coating	grey-green, white coating
Shape	Fibrous solid body
Format	1000 mm x 600 mm
Thickness	50 mm/60 mm
Rock wool melting point	1000 °C
Nominal bulk density	≥ 150 kg/m ³
Thermal conductivity [W/(m-K)]	λ _D 0.040 (acc. to DIN EN 13162)
Water vapour diffusion resistance factor	μ 1 (acc. to DIN EN 12086)
Pre-coating	PYRO-SAFE® FLAMMOTECT-A
Dry film thickness	approx. 0.5 mm – 0.7 mm
Storage	Store in a dry place
Safety information	Please note our safety data sheet.

Applications

Penetration seal

	Certification	System name	Fire resistance class
CE	ETA-14/0418	PYRO-SAFE® Flammotect single-layer	EI 90 acc. to EN 13501-2
		PYRO-SAFE® Flammotect double-layer	EI 120 acc. to EN 13501-2
		PYRO-SAFE® Flammotect quadruple-layer	EI 240 acc. to EN 13501-2
		PYRO-SAFE® Flammotect OSI	EI 120 acc. to EN 13501-2
DIN	Z-19.53-2329	PYRO-SAFE® Flammotect COMBI 90 PYRO-SAFE® Flammotect COMBI 90 V	Fire-resistant (90 min.)
	Z-19.53-2296	PYRO-SAFE® Flammotect 90	